



Stock code RIS-VENT2QR

The 2" or 3" B.S.P. adaptor is permanently installed on the vent stack - the valve part is "quick dis-connected" and replaced.

For replacement valve part only order Stock code RIS-VENTQR

Pressure setting 8oz per square inch (35mb)
 Vacuum setting 0.5oz per square inch (2mb)
 Size Inlet 2" or 3" B.S.P. (f)

Stock Code RIS-VENT3QR

MATERIALS:

Cap	Aluminium
Gauze	Stainless steel
Body	Aluminium (anodised and Teflon coated)
Valves	Brass (vacuum spring stainless steel)
Seat	Delrin™
Seals	Viton
Weight	1.64 kgs

- **Easy to remove for inspection / replacement**
- **Allows rapid change over of valves - leaves vents unprotected for minimum time**
- **No need for tools and risk of sparks**
- **Safer for personnel**
- Dead weight poppet - provides accurate relief characteristics
- Linear Teflon™ coated bearing design - has minimal contact area for low breakout force in sub-zero temperatures
- Drained seat detail - prevents ice build up in cold weather
- Reliable vacuum valve - proven design & materials
- Delrin™ poppet seat - for the best combination of sealing, fuel compatibility and long service life
- Environmentally friendly - upward discharge of vapour and minimal operating noise
- Heavy duty construction with anodised finish for long life in extreme environments
- Tested by Health & Safety laboratories to BS 7244:1990